

# TC SMUC2

## PRODUCT DATASHEET

### TC SMUC2 SODA DISPENSER

The industrial flow-through soda machine features a capacity of 154 liters per hour (2.6 liters per minute) and is equipped with a stainless steel coil. The machine does not include a tap head. It is designed to produce chilled soda water and chilled still water.

An optional installation package is available for purchase, which includes:

- 1 pcs 7-bar pressure regulator
- 1 pcs water filter housing
- 1 pcs water filter cartridge
- 1 pcs water pressure regulator
- 5 m plastic tubing and clamps

It requires a 230 V power supply and a water connection with a 1/2-inch externally threaded faucet. Any setup within a 1-meter radius of the machine is the responsibility of the customer.



### PRODUCT DETAILS

#### Dimensions

External size (mm)	566x438x770 (H)
Net weight (kg)	45
Gross weight (kg)	46
Tank (l)	42
Icebank (kg)	20
Compressor size (HP)	1/3
Input power (W)	450

Peak performance ice bank (l/h)	154
Voltage (V)	230
Current (A)	3,6
Max number of coils (pcs)	1 water + 1 soda
Refrigerant	R290a
Type of thermostat	mechanic

Compressor (kcal/h-10°C)	531
Accessories	Installation kit
Tap	no
Carbon water filter	no

#### THERMOTEKNIKA-CROWN COOL KFT.

BUDAPESTI BEMUTATÓTEREM ÉS KÖZPONT: H-1103 BUDAPEST,

KÔÉR U. 3/F TELEFON: +36 1 260 7126

thermotechnika@tchungary.com

[www.tchungary.com](http://www.tchungary.com)



**THERMOTEKNIKA  
CROWN COOL**